



# RP *Strike-03*™ RP *Strike-06*™

variant Can-Am Defender DPS/Max DPS



[www.RPAMS.com](http://www.RPAMS.com)

Bringing more **ASSETS** to the fight!

# RP *Strike-D3*™ RP *Strike-D6*™

variant Can-Am Defender DPS/Max DPS



## Standard Configuration

### RP Strike-D3™ & RP Strike-D6™

- RP Super Grit texture coating, tan or black
- RP tactical front bumper
- RP modular front cargo rack
- RP duel rear NATO litter restraint system
- Fox/Elka shock upgrade for high payload operations
- RP SOF Series II 12-PLY Run-Flat tires, 26x9x14 in
- 14-Inch wheels

### RECOMMENDED OPTIONS:

- RP high-load tactical team standoff nerf bar assembly/rock slider with stow and lock mode for air transport
- RP modular ammo/fuel can/payload assembly
- Elka high-performance shock absorbers
- Baja Designs blackout/IR lights & light bars
- Additional 12VDC & 24VDC outlets

### OPTIONAL EQUIPMENT:

- RP Powdercoat, custom colors available
- HydroGraphic Finishes, custom colors and patterns available
- RP SOF Spartan Series 12-PLY tires, 27x9x14 in front / 27x11x14 in rear
- Beadlock wheels
- HID/LED light illumination
- Antenna mount
- SatFi communication system/bundle
- Half and full windshields
- MEDEVAC Integration
- RP litter restraint, multi-modal and configurable rail system
- PowerAll® Jump Start System
- Initial spare parts kit
- Self-extracting 4500 lb winch



## VEHICLE SPECIFICATIONS

- 976 cc, 72 hp, heavy-duty HD10 Rotax® V-Twin, liquid-cooled with Intelligent Throttle Control and Electronic Fuel Ignition
- PRO-TORQ transmission with Quick Response System (QRS), high-airflow ventilation and Electronic Belt Protection, Extra - L / H / N / R / P. Dynamic Power Steering (DPS)
- Double A-arm front suspension, TTA-HD rear suspension with external sway bar
- True 4-mode traction system: 2x4 & 4x4 open rear differential, 2x4 & 4x4 locked rear differential with Visco-Lok QE auto-locking front differential
- Electronic Hill Descent Control
- ROPS-approved profiled cage, Certified ISO 3471 and OSHA

DRY WEIGHT <sup>1</sup>	Strike-D3	1,614-1,950 lb
	Strike-D6	1,857-1,950 lb
PASSENGERS	Strike-D3	3
	Strike-D6	6
DIMENSIONS <sup>2</sup>	Strike-D3	120 (L) x 62 (W) x 76 (H) in
	Strike-D6	152.5 (L) x 63.5 (W) x 76 (H) in
WHEELBASE	Strike-D3	83 in
	Strike-D6	115.5 in
GROUND CLEARANCE		11 in
FUEL CAPACITY		10.6 gal
PAYLOAD CAPACITY	Strike-D3	1,500 lb
	Strike-D6	1,750 lb
REAR BED CAPACITY		1,000 lb <sup>3</sup>
FRONT RACK CAPACITY		250 lb
TOWING CAPACITY		2,000 lb

<sup>1</sup> Estimated weight, depending on options.

<sup>2</sup> Standard Defender dimensions w/o RP Strike-Kit Upgrades

<sup>3</sup> California only: 600 lb.

### INFORMATION & DEALER INQUIRIES

Terry Wilmeth 971-237-3217, Nick Mooers 541-914-7543 or [CustomerService@RPAMS.com](mailto:CustomerService@RPAMS.com)



**RP Advanced Mobile Systems**

Veteran and Minority Owned Business

11160 SW Durham Lane, Suite 3 | McMinnville, Oregon 97128 | phone: 503-434-9446 | fax: 503-217-6080

[www.RPAMS.com](http://www.RPAMS.com)

The RP SOF tan tire may experience discoloration of the side wall under high temperatures. This discoloration does not compromise the quality of the tire. All pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication and are subject to change without notice. RP Advanced Mobile Systems, LLC assumes no responsibility for any inaccuracies, opinion, errors or omissions in those publications, nor fitness of purpose and non-infringement of intellectual property.

REV-12292017