



RP *Strike-M*TM RP *Strike-M4*TM

variant Can-Am Maverick DPS/Max DPS



www.RPAMS.com

Bringing more **ASSETS** to the fight!

RP *Strike-M*™

RP *Strike-M4*™

variant Can-Am Maverick DPS/Max DPS

Standard Configuration

RP Strike-M™ & RP Strike-M4™

- RP Super Grit texture coating, tan, black, camo
- RP high-capacity, multi-modal tactical payload flatbed
- RP multi-modal tailgate system for multiple tactical payload track configurations with Strike-M4 optional MEDEVAC integration
- RP tactical assault push bumper with strut integrated payload track system and aerial transport tie-downs
- Upgraded suspension for high payload operations
- Forward/rear 2-inch receivers
- ITP Delta steel wheels
- RP SOF Series II, 12-PLY Run-Flat tires, 26x9x12 in
- RP Fatigue Mitigation Tactical Seat System (MOLLE, 1000D Cordura®)
- RP soft roof (MOLLE, 1000D Cordura®)
- M4 ONLY: includes rear seating with Best-In-Class leg room, seats fold forward for Stokes/NATO litter carriage in bed

RECOMMENDED OPTIONS:

- RP high-load tactical team standoff nerf bar assembly/rock slider with stow and lock mode for air transport
- RP modular ammo/fuel can/payload assembly
- Beadlock wheels
- Elka high-performance shocks
- Baja Designs blackout/IR lights & light bars
- Additional 12VDC & 24VDC outlets

OPTIONAL EQUIPMENT:

- RP Powdercoat, HydroGraphic Finishes, custom colors and patterns available
- Narrowing Kit: A-arms and trailing arms
- RP modular front cargo rack
- RP quick release articulating roll cage for internal aerial transport
- RP SOF Series II 12-PLY Run-Flat tires, 26x9x14 in
- Apache 360 LT Track System
- Selectable RODS (Rear Open Differential System)
- RP keyless ignition
- HID/LED light illumination
- RP integrated seat hydration packs
- RP 4-point static retractable quick release harness kit
- SatFi communication system/bundle
- Antenna mount
- Half windshield
- RP MEDEVAC Integration
- RP litter restraint, multi-modal and configurable rail system
- PowerAll® Jump Start System
- Initial spare parts kit
- Self-extracting 4500 lb winch



RP Strike-M



RP Strike-M



RP Strike-M4

VEHICLE SPECIFICATIONS

- 976 cc, 101 hp, 1000R Rotax® V-Twin with high-flow dynamics, liquid-cooled, Intelligent Throttle Control with Electronic Fuel Ignition, Mid-engine layout for mass centralization
- CVT with Zylon-reinforced belt, L / H / N / R / P. Tri-Mode Dynamic Power Steering (DPS)
- Double a-arm front suspension with sway bars and torsional trailing a-arms independent rear suspension with sway bars
- Selectable 2WD / 4WD shaft driven with Visco-Lok QE auto-locking front differential
- High-strength 2-inch diameter steel cage, ROPS-approved
- Anti-Theft: Digitally Encoded Security System (D.E.S.S.™)

DRY WEIGHT	1,700 – 1,950 lb	
DIMENSIONS	Strike-M	129 (L) x 64 (W) x 74.2 in (H) 129 (L) x 60 (W) x 60 in (H) with narrowing kit and retracted roll cage
	Strike-M	159 (L) x 64 (W) x 78 in (H) 159 (L) x 60 (W) x 60 in (H) with narrowing kit and retracted roll cage
WHEELBASE	Strike-M 84.3 in / Strike-M 113.8 in	
GROUND CLEARANCE	Strike-M 13 in / Strike-M 12.5 in	
FUEL CAPACITY	10 gal	
PAYLOAD CAPACITY	Strike-M 1,500 lb / Strike-M4 2,000 lb	
REAR BED CAPACITY	1,000 lb	
OPTIONAL FRONT RACK CAPACITY	250 lb	
TOWING CAPACITY	1,500 lb	

INFORMATION & DEALER INQUIRIES

Terry Wilmeth 971-237-3217, Nick Mooers 541-914-7543 or CustomerService@RPAMS.com



RP Advanced Mobile Systems

Veteran and Minority Owned Business

11160 SW Durham Lane, Suite 3 | McMinnville, Oregon 97128 | phone: 503-434-9446 | fax: 503-217-6080

www.RPAMS.com

The RP SOF tan tire may experience discoloration of the side wall under high temperatures. This discoloration does not compromise the quality of the tire. All pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication and are subject to change without notice. RP Advanced Mobile Systems, LLC assumes no responsibility for any inaccuracies, opinion, errors or omissions in those publications, nor fitness of purpose and non-infringement of intellectual property. REV-10202017